

VSK Classic Light

Breathable membrane with completely self-adhesive surface
Riwega | eternitycomfort

Declaration of performance
Identification no.: DoP 1606/2013/06/11

1	Product Type: Unique identification code of the product-type.	02065010 VSK Classic Light						
2	Type batch or serial number or any other element allowing identification of the construction product as required under Article 11(4)	See label on product						
3	Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer	Breathable membrane for pitch roof and wall						
4	Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5)	VSK Classic Light Riwega srl, I - 39044 Egna (BZ), Via Isola di Sopra 28						
5	Contact Address: Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2)	Not used						
6	System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as set out in CPR, Annex V	System 3						
7	Notified body (hEN): In case of the declaration of performance (DoP) concerning a construction product covered by a harmonized standard	EN 13859-1; EN 13859-2, System 3: Following notified bodies have carried out the type approvals System 3						
		<table border="1"> <thead> <tr> <th>Testing Institut</th> <th>Identification number</th> <th>Report No.</th> </tr> </thead> <tbody> <tr> <td>tbu</td> <td>0799</td> <td>1.1/26921/0819.0.1</td> </tr> </tbody> </table>	Testing Institut	Identification number	Report No.	tbu	0799	1.1/26921/0819.0.1
Testing Institut	Identification number	Report No.						
tbu	0799	1.1/26921/0819.0.1						
8	Notified body (ETA): In case of the declaration of performance concerning a construction product for which a European Technical Assessment (ETA) has been issued	Not relevant						
9	Declared performance							

Essential characteristics	Performance	Method
Roll length	50 m	EN 1848-2
Roll width	1.50 m (+1.0 / -0.4 %)	EN 1848-2
Areal mass	235 g/m ² (±10 g/m ²)	EN 1849-2
Resistance to water penetration	W1	EN 1928 Method A
Air layer equivalent to the vapour passage	Sd = 0.2m (+0.05/-0.05m)	DIN EN ISO 12572
Fire reaction	Class E	EN 13501-1
Tensile strength MD/CD*	290/225 N/50 mm (±35/±25N/50 mm)	EN 12311-1
Elongation MD/CD*	65/90 % (±20%)	EN 12311-1
Resistance to tearing MD/CD*	170/200 N (±30N)	EN 12310-1
Flexibility at low temperature	-40°C	EN 1109
After artificial ageing		EN 13859-1; EN13859-2
Resistance to water penetration	W1	EN 1928 Method A
Tensile strength MD/CD*	280/175 N/50 mm (±30N/50 mm)	EN 12311-1
Elongation MD/CD*	≥ 65%**	EN 12311-1
Hazardous substances	No	
ZVDH classification according to the product data sheet	UDB-USB-A	Suitable as temporary cover, with accessories approved by the manufacturer
Driving rain test TU Berlin	Passed	
Temperature resistance	-40 °C / + 100 °C	
Accessories	Available	

*MD=machine direction; CD= cross direction; **from the initial value

10 Declaration: The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the manufacturer by the managing directors:



Rizzi Werner



Gamper Werner

Egna, 12/08/2021