Construction specification



Construction specification

of: 28/05/2018

TIROLL Air

Under-ridge roll Riwega | eternitycomfort Red-Brown Art. 01014321 (320mm) / 01014371 (370mm) / 01014391 (400mm) Brown Art. 01014322 (320mm) / 01014372 (370mm) / 01014392 (400mm) Copper Art. 01016325 (320mm) / 01016375 (370mm) / 01016395 (400mm) Rev.04 of: 03/09/2021

Supply and installation of the Riwega TIROLL AIR under-ridge roll, in the colour and size appropriate to the type of roofing. Universal 40 mm opening lath holders, 4x5 cm wooden battens and aluminium ridge tile hooks suitable for the type of ridge tile are used for professional fixing. To ensure correct adhesion, the surface of the tile/tile cover must be checked and it must be dry and dust-free.

Material Aluminium / Copper

Colour Red-brown / Brown / Copper

Measures 320 / 370 / 400 mm Airflow (DIN 4108-3) > 90 cm²/m (each side)

Alu development 1,20 % **Butylic Glue** 90 g/m UV rays stability stable

Supplier: Riwega Srl, via Isola di Sopra 28, 39044 Egna (BZ) – I

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website www.riwega.com. This document replaces the previous version.