

# UNI Air ROLL

Under-ridge roll  
Riwega | eternitycomfort

Construction specification

of: 11/08/2017

Red-Brown Art. 01010300 (310mm) / 01010310 (370mm) / 01010400 (400mm)

Brown Art. 01010301 (310mm) / 01010311 (370mm) / 01010401 (400mm)

Rev.03 of: 03/09/2021

Supply and installation of the under-ridge roll Riwega UNI AIR ROLL, in the colour and size appropriate to the type of roofing. Universal 40 mm opening lath holders, 4x5 cm wooden battens and aluminium ridge tile hooks suitable for the type of ridge tile are used for professional fixing. To ensure correct adhesion, the surface of the tile/tile cover must be checked and it must be dry and dust-free.

|                      |                          |
|----------------------|--------------------------|
| Material             | alu.PP.alu               |
| Colour               | Red-Brown / Brown        |
| Measures             | 310 mm / 370 mm / 400 mm |
| Alu development      | 1,35 %                   |
| Airflow (DIN 4108-3) | >145 cm <sup>2</sup> /m  |
| Butylic Glue         | 120 g/m                  |
| UV rays stability    | stable                   |

Supplier: Riwega Srl, via Isola di Sopra 28, 39044 Egna (BZ) – I

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website [www.riwega.com](http://www.riwega.com). This document replaces the previous version.