

Venti-tech Metal

Rigid under-ridge element
Riwega | eternitycomfort

Construction specification
of: 05/05/2014

Art. 01023001 Red-Brown ALU / 01024001 Red Brown PB / 01024004 Natural
Rev.03 of: 03/09/2021

Supply and installation of the Riwega Rigid under-ridge element VENTI-TECH METAL, in the colour and size appropriate to the type of roofing. Universal 40 mm opening lath holders, 4x5 cm wooden battens and aluminium ridge tile hooks suitable for the type of ridge tile are used for professional fixing. To ensure correct adhesion, the surface of the tile/tile cover must be checked and it must be dry and dust-free.

Material central part	Galvanized iron
Material side stripes	Aluminium / lead
Colour	Red-brown / Lead natural
Thickness	0,15 mm (Alu) / 0,30 mm (Lead)
Top stripe's thickness	Min. 150 mm
Under-ridge's width	Max. 400 mm
Length	1 m
Side stripe's height	125 mm
Airflow (DIN 4108-3)	> 100 cm ² /m (each side)
Butylic adhesive stripes	YES (only alu tape)

Supplier: Riwega Srl, via Isola di Sopra 28, 39044 Egna (BZ) – I

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website www.riwega.com. This document replaces the previous version.