

Tape UV

Polyethylene adhesive tape, super UV stable
Riwega | eternitycomfort

Technical data sheet

of 28/05/2020

Art. 02040183 - 02040181 - 020103533

Rev.08 of 31/10/2022



PROPERTIES	Tape UV 60	Tape UV 80	Tape UV 300 X
Article	02040183	02040181	020103533
Measurements	60 mm x 25 m	80 mm x 25 m	300 mm x 25 m
Colour	Black		
Adhesive	Solvent and emollient free acrylic based adhesive		
Adhesive backing	PP - Film (100 µm)		
Adhesive weight	210 g/m ² (DIN EN ISO 536)		
Reinforcement	PET mesh		
Thickness (without cover)	0,30 - 0,32 mm (DIN EN 14410)		
Covering material	Silicone liner		Silicone liner (precut 150 mm + 150 mm)
Tear strenght with elasticity	≥ 60 N/25 mm; 450 % (DIN EN 14410)		
Application temperature	+5 °C / +30 °C (workable from -10 °C)		
Operating temperature	-30°C / +100°C		
Sd value	Approx. 16 m		
Resistance to detachment	Passed (DIN 4108-11)		
Resistance to condensation	Very high		
Resistance to aging	Very high		
Initial adhesion (<i>tack</i>)	Very high		
UV stability	24 months*		
Packaging	10 rolls	6 rolls	2 rolls
Storage	Cool and dry away from UV rays, max. 24 months		
Storage temperature	+18°C / +25°C		

*Referring to the Central Europe climate

Riwega S.r.l. reserves the possibility to review or change these technical values. The updated technical data sheet can be found on the website www.riwega.com.
This data sheet replaces the previous copy.