

Tape 1 PAP

Polyethylene adhesive tape specifically for interior use Riwega | eternitycomfort

Construction specification of: 01/01/2016

Art. PAP 02040150 - PAPX 02040151 - PAPX3 02040152

Rev.04 of: 11/08/2021

Supply and installation of Riwega TAPE 1 PAP adhesive tape, consisting of a PE treated paper film coated with acrylic adhesive, for air, steam and noise sealing of the following points:

- overlaps of the Riwega USB steam screens on the roof and/or wall with indoor installation;
- junctions between Riwega USB steam screens and the surface of chimneys, windows, vents or other indoor installation
- joints of panel walls or OSB-type panels in the construction of wooden houses.

Also available in versions:

- TAPE 1 PAP X with liner cut in half (30+30 mm) to facilitate the joining of the internal corners of wooden panel walls or OSB panels:
- TAPE 1 PAP X3 with liner cut in three parts (30+15+15 mm) to facilitate the joining of the internal corners of wooden panel walls or OSB panels and the sealing between frame and wooden wall.

The installation must be completed with a strong pressure using a special roller to make 100% of the adhesive base adhere perfectly to the surface to be sealed.

Supplier: Riwega Srl, via Isola di Sopra 28, 39044 Egna (BZ) - I

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website www.riwega.com. This document replaces the previous version.