

# Tape ICE

Acrylic adhesive tape suitable at low temperatures  
Riwega | eternitycomfort

Technical data sheet  
of: 26/11/2019  
Art. 02040165  
Rev.02 of: 31/10/2022

Properties	
Measurements	60 mm x 25 m
Colour	Silver film with white writing
Adhesive	Polyacrylate-based dispersion adhesive, free of solvents and plasticizers
Adhesive backing	LDPE-Film (70 µm)
Adhesive density	200 g/m <sup>2</sup> (DIN EN ISO 536)
Reinforcement	PET-mesh
Thickness (without liner)	0,26 - 0,28 mm (DIN EN 1942)
Covering material	Siliconized liner
Tear strength with elasticity	≥ 25 N/25 mm; 50% (DIN EN 14410)
Working temperature	+5 °C / +30 °C (workable from -20°C)
Operating temperature	-30 °C / +100 °C
Sd value	approx. 11 m
Resistance to detachment	Compliant (DIN 4108-11)
Resistance to condensation	Very high
Resistance to ageing	Very high
Initial adhesion ( <i>tack</i> )	Very high
UV stability (Adhesive backing)	24 months*
Packaging	10 rolls
Storage	Store in the original and unopened packaging, in a dry and well ventilated place at a temperature between +18°C and +25°C, for max. 24 months



\* referring to the Central Europe climate

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website [www.riwega.com](http://www.riwega.com). This document replaces the previous version.