

AIR Stop Radon RGD100

Self-adhesive system with aluminium base and radon gas certified EPDM collar
Riwega | eternitycomfort

Technical data sheet
of: 06/12/2024
Art. 02203543
Rev.00 of: -

Properties	
Technical data - Adhesive strip	
Material	Surface ALU / Butyl glue
Colour	Brown / Black
Thickness	Approx. 1 mm Alu / Approx. 1 mm butyl
Butyl density (DIN EN ISO 10563)	Approx. 1.5 g/cm ³
Operating temperature	-40°C / +100°C
UV-Stability	Very good
Technical data - EPDM collar	
Material	EPDM
Colour	Black
Hardness (DIN ISO 7619-1)	60 ±5 Shore A
Density (DIN ISO 1183-1)	Approx. 1.09 g/cm ³
Tensile strength (DIN 53504)	15 MPa
Elongation at break (DIN 53504)	630%
Operating temperature	-30°C / +100°C
General data	
Working temperature	+5°C / +30°C
Bitumen compatibility	Yes
Halogen-free	Yes
Number of openings	1
Base size	320 x 320 mm
Inside diameter of the EPDM collar	100 mm - 110 mm
Type of application	Tubes: ventilation for bathrooms, chimney hoods, gas, etc.
Packaging	4 pieces
Storage	Store in a dry place at about 20°C, away from dust

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website www.riwega.com. This document replaces the previous version.