

FDB EXT AC

Acrylic adhesive tape for windows / EXTERNAL USE
Riwega | ertilitycomfort

Technical data sheet

of: 06/02/2014

Art. N° 02045612-02045613-02045614

Rev.08 of: 19/04/2024

Characteristic	Method	FDB EXT AC 75	FDB EXT AC 100	FDB EXT AC 150
Article		02045612	02045613	02045614
Adhesive		Modified polyacrylate		
Adhesive support		PET.PP.PET		
Mass per unit area	EN 1849-2	120 g/m ²		
Liner		White film		
Roll width		75 mm	100 mm	150 mm
Roll length		30 m		
Colour		White		
Thickness	EN 1849-2	0,37 mm		
Tensile strength MD*	EN 12311-1	290 N/50mm		
Tensile strength CD*	EN 12311-1	31 N/50mm		
Elongation MD*	EN 12311-1	19 %		
Elongation CD*	EN 12311-1	130 %		
Sd value	EN 1931	0,04 m		
Resistance to water penetration	EN 1928 Method A	W1		
Working temperature		+5°C / +40°C (from -10 °C workable)***		
Temperature resistance		-40°C / +80°C		
Fire reaction class	EN 13501-1	Class E		
UV-stability		3 months**		
Packaging		5 rolls	4 rolls	2 rolls
Storage		Store in a cool and dry place for max. 12 months		

*MD= Machine Direction; CD= Cross Direction / **referring to the Central Europe climate / *** For optimizing adhesion at temperatures lower than +5 °C, the use of Primer Spray is recommended.

Riwega S.r.l. reserves the possibility to review or change these technical values. The updated technical data sheet can be found on the website www.riwega.com. This data sheet replaces the previous copy.