

FDB Vario Plus FL

Acrylic adhesive tape with variable hygrometry with additional adhesive strip
Riwega | eternitycomfort

Technical data sheet

of: 01/06/2017

Art. N° 020458071-020458101-020458151

Rev. 05 of: 30/10/2022



Characteristic	Method	FDB Vario 75 Plus FL	FDB Vario 100 Plus FL	FDB Vario 150 Plus FL
Article		020458071	020458101	020458151
Adhesive		Acrylic with "Fingerlift"		
Adhesive support		PET.PA		
Colour		White		
Roll width		75 mm	100 mm	150 mm
Roll length		25 m		
Density (total)	EN 1849-2	400 g/m ²		
Thickness	EN 1849-2	0,63 mm		
Pre-cut liner		(50 + 25) mm	(75 + 25) mm	(65 + 60 + 25) mm
Tear resistance	EN 12311-1	MD* = 300 N/50mm (±15%) / CD* = 55 N/50mm (±15%)		
Elongation at break	EN 12311-1	MD* = 25 % (±15%) / CD* = 135 % (±15%)		
Resistance to water penetration	EN 13984 / EN 1928	W1		
Water column		> 2000 mm		
Air permeability	EN 1026	a _n ≤ 0,1 m ³ /m ² h		
Heavy rain test	EN 1027	> 600 Pa		
S _d value	EN 1931 / EN 12572 PB 4.1 / 12-134-1 MPFA	0,5 m ≤ S _d ≤ 20 m		
Fire reaction	EN ISO 11925-2: 2010	Class E		
UV-stability		6 months**		
Temperature resistance		- 40°C / +80°C		
Working temperature		- 10°C / +40°C		
Packing (rolls per box)		5 (5 x 25 m = 125 m)	4 (4 x 25 m = 100 m)	2 (2 x 25 m = 50 m)
Storage		Store in a cool and dry place, in the original packaging, for max. 12 months		

*MD= longitudinal; CD= transversal / **referring to the Central Europe climate

Riwega S.r.l. reserves the possibility to review or change these technical values. The updated technical data sheet can be found on the website www.riwega.com.
This data sheet replaces the previous copy.