ROLL-tech

QUICK OVERVIEW: STRENGTHS

The first, the original

- Under-ridge roll
- Water resistant and UV stable
- Guarantees strong air passage
- Central part in reinforced PP and perfectly adaptable folded aluminium stripe
- Prefolded aluminium edge to increase mechanical resistance





Composition:

- 1) Aluminium with prefolded edge
- ² Seam
- 3 UV stabilized PP
- (4) Reinforced PP fabric
- (5) Extruded butylic glue
- 6 Silicon liner

Features:













Technical data sheet		
Material		alu.PP.alu
Pre-folded edge		YES
Aluminium stripe		0,15 mm
Roll legth		5,00 m
Central fabric		UV stabilized PP
Central stripe		reinforced PP fabric
Material assembly		glue and seam
Extruded butylic glue		140 g/m
Air flow (each side)	DIN 4108-3	>145 cm²/m
UV rays stability		stable
Ageing resistance		>10 years (indirect exp.)
Temperature resistance		-30°C /+70°C
Processing temperature		+5°C /+40°C
Alu development		1,45%
Storage		dry, protected from UV rays, max. +30°C
Packaging		2 pc/box
Pallet		60 boxes

Colours / Measures	310 mm	350 mm	370 mm	400 mm
Red-brown	01013101	01013501	01013601	01014001
Brown	01013102	01013502	01013602	01014002
Black	01013103	-	01013603	-
Beige	-	-	01013606	-
Grey	01013104	-	-	-