

Coll 150 X

Single-sided butyl adhesive strip with pre-cut liner
Riwega | eternitycomfort

Technical data sheet
of: 03/08/2017
Art. 02044151
Rev.04 of: 13/08/2021

Properties	
Article no.	02044151
Material	Butyl / LDPE-film
Liner	PE (pre-cut liner)
Measurements	150 mm x 15 m
Thickness	2 mm
Colour	Grey
Weight (DIN EN ISO 1183-1)	approx. 1,40 g/cm ³
Application temperature	+5°C / +30°C
Service temperature	-40°C / +100°C
Hardness - Shore00 (DIN EN ISO 868)	approx. 40
Viscosity (DIN EN ISO 7390)	Stable
Ignition temperature (DIN 51794)	>400°C
Compression resistance (DTU 39.4)	>0,04 N/mm ²
Solid content (DIN EN ISO 10563)	>99 %
Fire behavior (DIN 4102)	B2, normally flammable
UV-stability	3 months*
Emissions (Emicode®)	Very low
Packaging	2 rolls
Storage	Store in a dry place at approximately 20°C, out of direct sunlight for a maximum of 12 months

* referring to the Central Europe climate

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website www.riwega.com. This document replaces the previous version.