

FDB Vario NET

Variable Sd acrylic adhesive tape with plasterable net
Riwega | eternitycomfort

Technical data sheet

of: 18/10/2019

Art. 02045775

Rev.02 of: 19/08/2021

Properties	
Measurements	75 mm x 30 m
Fiberglass mesh base	100 mm
Adhesive side A	Acrylate (20 mm wide strip)
Adhesive side B	
Adhesive backing	Non-woven fabric in PET / PVC
Colour	White
Covering material side A	Silicone liner
Covering material side B	
Emissions	Very low according to EMICODE ®
Sd value	0,03 - 15 m (EN ISO 12572)
Permeability coefficient (joints)	$a \approx 0 \text{ m}^3 / [\text{h} \cdot \text{m} \cdot (\text{daPa})^n]$ (EN 1026)
Watertightness with driving rain (joints)	$\geq 1050 \text{ Pa}$ (EN 1027)
Fire resistance class	E (EN 13501-1)
Working temperature	+5°C / +45°C
Operating temperature	-40°C / +80°C
UV stability (Adhesive backing)	6 months (referring to the Central Europe climate)
Packaging	4 rolls
Storage	Cool and dry away from UV rays, max.12 months
Storage temperature	+1°C / +20°C

Riwega S.r.l. reserves to review or change these technical values. You can find the technical data sheet on the website www.riwega.com. This data sheet replaces the previous copy.