

# ROLL Flex TOP - Cu

Pleated strip connector  
Riwega | eternitycomfort

Rev.03

Technical data sheet  
of 29/05/2014  
of 02/09/2021

| Essential characteristics | Value   |
|---------------------------|---|
| Material                  | Copper / Butyl  |
| Covering material         | Pre-cut silicone liner                                    |
| Thickness (copper)        | 0,10 mm   |
| Thickness (butyl glue)    | 1,5 mm  |
| Roll length               | 5 m   |
| UV stability              | Stable*   |
| Resistance to aging       | Resistant   |
| Resistance to temperature | -30 °C / +90 °C   |
| Working temperature       | +5 °C / +40 °C  |
| Aluminium elongation      | 1,30%   |
| Storage                   | Dry, protected from UV rays, max.+30°C for max. 24 months |
| Packaging                 | 1 piece / box   |
| Pallet                    | 48 Boxes  |

## Article and measurements

|                        |          |
|------------------------|----------|
| Colours / Measurements | 300 mm   |
| Copper                 | 01108305 |

\* Referring to the Central Europe climate

Riwega S.r.l. reserves the possibility to review or change these technical values. The updated technical data sheet can be found on the website [www.riwega.com](http://www.riwega.com). This data sheet replaces the previous copy.