

# ROLL-tech

Under-ridge rolls  
Riwega | eternitycomfort

Technical data sheet

of 12/03/2020

Rev.06

of 09/03/2022

Article and measurements				
Colours / Measurements	310 mm	350 mm	370 mm	400 mm
Red brown	01013101	01013501	01013601	01014001
Brown	01013102	01013502	01013602	01014002
Black	01013103	-	01013603	-
Beige	-	-	01013606	-
Grey	01013104	-	-	-

Properties	
Material	alu.PP.alu
Pre-folded border	Yes
Alu thickness	0,15 mm
Roll length	5 m
Central netting	UV stabilized polypropylene
Reinforced central band	Reinforced polypropylene fabric
Materials assembly	Glue and single seam
Butyl glue	140 g/m
Air permeability per part (DIN 4108-3)	>145 cm <sup>2</sup> /m
UV-Stability	Stable
Resistance to ageing	>10 years (with indirect radiation)
Temperature resistance	-30°C / +70°C
Working temperature	+5°C / +40°C
Aluminium elongation	1,45%
Storage	Keep the product in its original packaging, dry, protected from UV rays, at a temperature of max.30°C
Packaging	2 pieces (10 m)
Pallet	60 boxes (600 m)

Riwega S.r.l. reserves the possibility to review or change these technical values. The updated technical data sheet can be found on the website [www.riwega.com](http://www.riwega.com). This data sheet replaces the previous copy.