

# Sil AC

Acrylic acid esters-based copolymer sealant  
Riwega | eternitycomfort

Technical data sheet  
of: 06/02/2014  
Art. 02040400-02040401  
Rev.03 of: 16/08/2021

Properties	Cartridge	Tube
Article	02040400	02040401
Material	Copolymer based on acrylic acid esters with additives	
Content	310 ml	600 ml
Density	Approx. 1,0 g/cm <sup>3</sup> (DIN EN ISO 1183-1)	
Viscosity	Pasty and thixotropic consistency (DIN EN ISO 7390)	
Skin formation (23°C, 50% RH)	Immediate adhesion, starting at about 30 minutes	
Drying time	From 1 to 7 days, depending on the surfaces porosity, the temperature and the quantity of product applied	
Average yield	Approx. 30 / 40 g/m, depending on the diameter application	
Working temperature	-5°C / +40°C	
	Recommended da +5°C	
Operating temperature	-30°C / +80°C	
Colour	Yellow	
Packaging	20 cartridges of 310 ml	20 bags of 600 ml
Storage	Cool and dry away from UV rays, max. 12 months	

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website [www.riwega.com](http://www.riwega.com). This document replaces the previous version.