

Tape 1 PAP

Polyethylene adhesive tape specifically for interior use
Riwega | eternitycomfort

Technical data sheet

of 06/02/2014

Art. 02040150 - 02040151 - 02040152

Rev.06 of 11/08/2021

PROPERTIES	Tape 1 PAP	Tape 1 PAP X	Tape 1 PAP X3
Article	02040150	02040151	02040152
Measurements	60 mm x 25 m		
Colour	Yellow		
Adhesive	Solvent and emollient free acrylic based adhesive		
Adhesive backing	Paper with PE coating (120 µm)		
Adhesive weight	210 g/m ² (DIN EN ISO 536)		
Reinforcement	None		
Thickness (without cover)	0,32 - 0,34 mm		
Covering material	Silicone liner	Synthetic liner cut in half lengthwise (30 + 30 mm)	Synthetic liner cut into three sections (30 + 15 + 15 mm)
Tear strenght with elasticity	≥ 150 N/25mm; 3-5 % (DIN EN 14410)		
Application temperature	+5 °C / +30 °C		
Operating temperature	-30 °C / +100 °C		
Sd value	Approx. 5 m		
Resistance to detachment	Passed (DIN 4108-11)		
Resistance to condensation	Very high		
Resistance to aging	Very high		
Initial adhesion (<i>tack</i>)	Very high		
Packaging	10 rolls		
Storage	Cool and dry away from UV rays, max. 24 months		
Storage temperature	+18 °C / +25 °C		

Riwega S.r.l. reserves the possibility to review or change these technical values. The updated technical data sheet can be found on the website www.riwega.com.
This data sheet replaces the previous copy.