

# Tape 2 BU

Double-faced butyl adhesive strip  
Riwega | eternitycomfort

Rev.06

Technical data sheet  
of 06/02/2014  
Art. 02040315  
of 11/09/2023

PROPERTIES		
Product	Tape 2 BU 20 mm	Tape 2 BU 50 mm
Article	02040315	02040350
Material	Butyl	
Liner	PE with Fingerlift	
Measurements	20mm x 25m	50mm x 35m
Thickness	1,5 mm	1,0 mm
Colour	Black	
Weight	ca.1,3 g/cm <sup>3</sup> (DIN EN ISO 1183-1)	ca.1,5 g/cm <sup>3</sup>
Application temperature	+5°C/+30°C	+0°C/+40°C
Service temperature	-40°C/+100°C	
Hardness (Shore00)	approx.30 (DIN EN ISO 868)	npd*
Vertical sliding	npd*	0mm (ISO 7390)
Viscosity	Stable up to 100°C (DIN EN ISO 7390)	
180° Peel Adhesion	npd*	22 N/cm (ASTM D 1000)
180° Peel Adhesion at 5°C on concrete	npd*	20 N/cm
Probe Tack	npd*	7.2 N (ASTM D 2979)
Compression resistance	>0,03 N/mm <sup>2</sup> (DTU 39.4)	npd*
Solid content	>99% (DIN EN ISO 10563)	100%
Ignition temperature	>400°C (DIN 51794)	npd*
Fire behavior	B2 (DIN 4102)	E (EN 13501-1)
Emissions	Very low (according to Emicode®)	
Packaging	14 rolls	8 rolls
Storage	Store in a dry place at approximately 20°C, out of direct sunlight for a maximum of 12 months	

\*npd = no performance determined

Riwega S.r.l. reserves the possibility to review or change these technical values. The updated technical data sheet can be found on the website [www.riwega.com](http://www.riwega.com). This data sheet replaces the previous copy.

