

Tape BOLD

Reinforced and double-faced acryl adhesive mass
Riwega | eternitycomfort

Technical data sheet

of 03/08/2017

Art. 02040210

Rev.04 of 13/08/2021

| PROPERTIES | |
|----------------------------------|---|
| Measurements | 10 mm x 12 m |
| Colour | Transparent |
| Adhesive | Solvent and emollient free acrylic based adhesive |
| Adhesive backing | None |
| Adhesive weight | 1750 g/m ² |
| Reinforcement | PET mesh |
| Thickness (without cover) | 1,50 - 2,00 mm (DIN EN 1942) |
| Covering material | Silicone liner |
| Adhesive strength (AFERA 5001) | ≥ 25 N/25 mm |
| Application temperature | +5 °C / +30 °C |
| Operating temperature | -30°C / +80°C |
| Resistance to condensation | High |
| Resistance to aging | High |
| Initial adhesion (<i>tack</i>) | High |
| Packaging | 10 rolls |
| Storage | Cool and dry away from UV rays, max. 24 months |
| Storage temperature | +18 °C / +25 °C |

Riwega S.r.l. reserves the possibility to review or change these technical values. The updated technical data sheet can be found on the website www.riwega.com.
This data sheet replaces the previous copy.