

Tape Rapid

Single-sided acrylic tape without liner
Riwega | eternitycomfort

Technical data sheet
of: 29/04/2019
Art. 02040162
Rev.02 of: 09/08/2021



| Properties | |
|-------------------------------|---|
| Measurements | 60 mm x 50 m |
| Colour | White |
| Adhesive | Solvent and emollient free acrylic based adhesive |
| Adhesive backing | LDPE PP-Film |
| Adhesive weight | 180 g/m ² (DIN EN ISO 536) |
| Reinforcement | PET mesh |
| Thickness (without cover) | 0,23 - 0,27 mm (DIN EN 14410) |
| Covering material | None |
| Tear strength with elasticity | ≥ 35 N/25mm; 400% (DIN EN 14410) |
| Application temperature | +5°C / +30°C |
| Operating temperature | -30°C / +120°C |
| Sd value | Approx.40 m |
| Resistance to detachment | Passed (DIN 4108-11) |
| Resistance to condensation | High |
| Resistance to aging | Very high |
| Initial adhesion (tack) | Very high |
| UV stability | 24 months* |
| Packaging | 10 rolls |
| Storage | Cool and dry away from UV rays, max.24 months |
| Storage temperature | +18°C / +25°C |

* referring to the Central Europe climate

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website www.riwega.com. This document replaces the previous version.