

Coll Vlies Plus

High Performance Self-Adhesive Butyl Sealing Tape with Polypropylene Fleece
Riwega | eternitycomfort

Technical data sheet
of: 06/02/2014
Art. 02044250 - 02044500
Rev.03 of: 21/07/2021



Properties	Coll Vlies Plus 250	Coll Vlies Plus 500
	Art. 02044250	Art. 02044500
Material	Polypropylene Fleece / Butyl Rubber Adhesive / Removable silicone liner	
Colour (Polypropylene Fleece / Butyl Rubber Adhesive)	White / Grey	
Width	250 mm	485 mm
Length	10 m	
Thickness	1 mm	
Tensile strength MD/CD* (EN 12311-1)	115 N/50mm / 100 N/50mm	
Elongation at break MD/CD* (EN 12311-1)	100 % / 100 %	
Solids	100 %	
180° Peel Adhesion (ASTM D 1000)	20 N/cm	
Probe Tack (ASTM D 2979)	8,0 N	
Vertical Flow (ISO 7390)	0 mm	
Cement Adhesive Strength C2E on Fleece (EN 12004 - EN1348)	0,9 N/mm ²	
Application temperature range	0°C / +40°C	
Service temperature range	-30°C / +90°C	
Total Volatile Organic Compound emissions TVOC (ISO 16000-6)	30 µg/m ³	
Packaging	2 rolls	1 roll
Storage	Store in the original and unopened packaging in a dry and well ventilated place at a temperature between +5 °C and +40 °C, for max. 12 months	

*MD= machine direction; CD=cross direction

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website www.riwega.com. This document replaces the previous version.