

Tape Green 100 X

Single-sided, adhesive tape in PE with acrylic glue, PET-scrim and pre-cutted liner
Riwega | eternitycomfort

Technical data sheet
of 28/11/2019
Art. 020401610
Rev.02 of 15/05/2023

PROPERTIES

Measurements	100 mm x 25 m
Colour	Green with black writing
Adhesive	Pure Polyacrylate, free of solvents and plasticizers
Adhesive backing	PE-Film (70 µm)
Adhesive density	200 g/m ²
Reinforcement	PET / PVA mesh
Thickness (without liner)	0,28 mm
Covering material	Silicone paper liner, pre-cut at 15/85mm (90 g/m ²)
Tear strenght with elasticity	≥ 22 N/10mm; 586 % (DIN EN 14410)
Adhesive strength (AFERA 5001)	≥ 25 N/25mm
Working temperature**	+5 °C / +30 °C
Operating temperature	-40 °C / +80 °C
Sd value	Approx. 40 m
Resistance to detachment	Compliant (DIN 4108-11)
Resistance to condensation	High
Initial adhesion (<i>tack</i>)	High
UV stability (Adhesive backing)	12 months*
Packaging	16 rolls
Storage	Cool and dry away from UV rays, max. 24 months
Storage temperature	+18 °C / +25 °C

* referring to the Central Europe climate

Riwega S.r.l. reserves the possibility to review or change these technical values. The updated technical data sheet can be found on the website www.riwega.com.
This data sheet replaces the previous copy.