


FDB Vario

20
R3



QUICK OVERVIEW: STRENGTHS

The universal window tape

- Acrylic adhesive tape with variable hygrometry
- Indoor & outdoor use, regulates the passage of vapour according to temperature and humidity
- Guarantees air, wind and waterproofing in the laying joint of windows and doors
- Waterproofing to air, water and wind
- Overplasterable surface

Features:



Classification:



Technical data sheet

Glue		acrylic with Fingerlift
Glue carrier material		PET.PA
Thickness	EN 1849-2	0,63 mm
Sd value		0,5 - 20 m
Air tightness	EN 1026	$a_n \leq 0,1$
Tightness against driving rain	EN 1027	>600 Pa
Tensile strength MD/CD*	EN 12311-1	300 / 55 N/50mm
Elongation at break MD/CD*	EN 12311-1	25 / 135 %
Water column		>200 cm
Resistance to water passage	EN 1928	W1
Fire reaction class	EN ISO 11925-2	E
VOC class	ISO 16000	A+
Working temperature		-10°C / +40°C
Temperature resistance		-40°C / +80°C
UV stability		6 months
Storage place		dry, protected from UV rays
Storage period		max. 12 months



Composition:

- Multilayer non-woven PET.PA ①
- Acrylic glue with Fingerlift (protruding liner) ②

Codes and measures

Version	Code	Measures (mmxm)	Box (pc)	Pallet (box)
75	02045807	75 (50+25) x25	5	96
100	02045810	100 (75+25) x25	4	96
150	02045815	150 (65+60+25) x25	2	96

*MD = longitudinal CD = transversal
Riwega Srl is not responsible for negligent and improper use of its products