


FDB EXT VSK Plus

24

R3




QUICK OVERVIEW: STRENGTHS

The complete adhesive tape for indoors, with reinforced surface

- Breathable adhesive tape
- Outside use
- Windtight sealing of door and window joints
- Increased weight for high mechanical strength
- Overplasterable surface

Features:



Technical data sheet

Glue		acrylic with Fingerlift
Glue carrier material		PP.PP
Thickness	DIN 53855	0,62 mm
Sd value	EN ISO 12572	0,08 m
Air tightness	EN 1026	$a_n \leq 0,1$
Resistance to water passage	EN 1928	W1
Tensile strength MD/CD*	EN 12311-1	290 / 31 N/50mm
Elongation at break MD/CD*	EN 12311-1	19 / 130 %
Water column		>200 cm
Fire reaction class	EN 13501-1	E
Working temperature		+5°C / +40°C
Temperature resistance		-40°C / +80°C
UV stability		6 months
Storage place		dry, protected from UV rays
Storage period		max. 12 months

Composition:

- Acrylic glue with silicone liner ①
- Multilayer non-woven PP.PP ②
- Acrylic glue with pre-cutted liner ③

Codes and measures

Version	Code	Measures (mmxm)	Box (pc)	Pallet (box)
85	02046108	85 (25+60) x25	4	72
100	02046110	100 (25+75) x25	4	72

*MD = longitudinal CD = transversal

Riwega Srl is not responsible for negligent and improper use of its products