

Air Coll



27

R3

QUICK OVERVIEW: STRENGTHS

Strong plastering adhesion

- Monoadhesive butyl band
- Excellent for stitches that require subsequent shaving
- Ideal for waterproofing the external sill support
- The pre-cut liner makes it ideal for all linear and corner seals
- Characterized by butyl glue with a high seal and without solvents, suitable for every laying surface



Composition:

- ① Non-woven fabric in PP
- ② Butylic glue
- ③ Pre-cutted silicone liner

Codes and measures

Version	Code	Measures (mmxm)	Box (pc)	Pallet (box)
Air Coll 75 X	02203207	75x25	4	30
Air Coll 150 X	02203215	150x25	2	30

Features:



Technical data sheet

Glue		butyl
Glue carrier material		non-woven fabric in PP
Protection liner		YES (pre-cutted)
Thickness		1,0 mm
Specific weight	DIN EN ISO 1183-1	~1,4 g/cm ³
Viscosity	DIN EN ISO 7390	stable
Hardness (Shore 00)	DIN EN ISO 868	~40
Compressive strength	DTU 39.4	>0,04 N/mm ²
Solid content	DIN EN ISO 10563	>99 %
Emissions	EMICODE®	very low
Working temperature		+5°C / +30°C
Temperature resistance		-40°C / +100°C
Fire class	DIN 4102	B2
UV stability		3 months*
Storage place		dry, protected from UV rays, ~20°C
Storage period		max. 12 months

*with reference to the Central European climate
Riwega Srl is not responsible for negligent and improper use of its products