


Accessories for USB Weld AS

58

R3



Seal INT (hot or cold weldable internal corner)


Code	020103531
Material	TPU
Measurements (Width x Length x H)	150 x 150 x 220 mm
Resistance to water passage	W1
Fire reaction class	E
Cold weldability	with solvent THF Welding Liquid
Hot weldability	with hot air 200°C / 300°C



Seal EXT (hot or cold weldable external corner)

Code	020103532
Material	TPU
Measurements (Width x Length x H)	350 x 350 x 140 mm
Resistance to water passage	W1
Fire reaction class	E
Cold weldability	with solvent THF Welding Liquid
Hot weldability	with hot air 200°C / 300°C

new
product



Seal DD (hot or cold weldable sealing collar)

Code	020103530
Material	TPU
Internal diameter	min. 90 mm - max. 125 mm
Base external diameter	250 mm
Fire reaction class	E
Cold weldability	with solvent THF Welding Liquid
Hot weldability	with hot air 200°C / 300°C



Bottle with brush

Code	PLA13601
Compatibility	welding solvents
Material	soft plastic



THF Welding Liquid

Code	02010352
Material	tetrahydrofuran (THF)
Content	1 l
Output	~10 ml/m (1 can ~100 m)
Applicatore	bottle with brush (PLA13601)
Working temperature	recommended +18°C / +20°C (workable >10°C)
Storage	dry, in the original can, max. 12 months