

# AIR Stop D1 (Φ 8 - 12 mm)

Self-adhesive system with base in aluminium and EPDM collar  
Riwega | eternitycomfort

Technical data sheet

of: 06/02/2014

Art. 02201508

Rev.04 of: 10/11/2022

<b>Properties</b>	
<b>Technical data - Adhesive strip</b>	
Material	Surface ALU / Butyl glue
Colour	Brown / Black
Thickness	Approx. 1 mm Alu / Approx. 1 mm butyl
Butyl density (DIN EN ISO 10563)	Approx. 1.5 g/cm <sup>3</sup>
Operating temperature	-40°C / +100°C
UV-Stability	Very good
<b>Technical data - EPDM collar</b>	
Material	EPDM
Colour	Black
Hardness (DIN ISO 48)	60 ±5 Shore A
Density (DIN ISO 1183-1)	Approx. 1.15 g/cm <sup>3</sup>
Tensile strength (DIN ISO 37)	11.6 MPa
Operating temperature	-30°C / +100°C
UV stability	Very good
<b>General data</b>	
Working temperature	+5°C / +30°C
Bitumen compatibility	Yes
Halogen-free	Yes
Number of openings	1
Base size	150 x 150 mm
Inside diameter of the EPDM collar	8 mm - 12 mm
Type of application	Tubes: electrical, telephone, aerial, satellite dish, data, etc.
Packaging	10 pieces
Storage	Store in a dry place at about 20°C, away from dust

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website [www.riwega.com](http://www.riwega.com). This document replaces the previous version.