

AIR Stop FRGD100

Self-adhesive system with base in aluminium and EPDM collar
Riwega | eternitycomfort

Technical data sheet
of: 06/02/2014
Art. 02203510
Rev.04 of: 14/11/2022

Properties	
Technical data - Adhesive strip	
Material	Surface ALU / Butyl glue
Colour	Brown / Black
Thickness	Approx. 1 mm Alu / Approx. 1 mm butyl
Butyl density (DIN EN ISO 10563)	Approx. 1.5 g/cm ³
Operating temperature	-40°C / +100°C
UV-Stability	Very good
Technical data - EPDM collar	
Material	EPDM
Colour	Black
Hardness (DIN ISO 48)	60 ±5 Shore A
Density (DIN ISO 1183-1)	Approx. 1.15 g/cm ³
Tensile strength (DIN ISO 37)	11.6 MPa
Operating temperature	-30°C / +100°C
UV stability	Very good
General data	
Working temperature	+5°C / +30°C
Bitumen compatibility	Yes
Halogen-free	Yes
Number of openings	1
Base size	350 x 350 mm
Inside diameter of the EPDM collar	100 mm – 125 mm
Type of application	Tubes: ventilation for bathrooms, chimney hoods, gas, etc.
Packaging	2 pieces
Storage	Store in a dry place at about 20°C, away from dust

Riwega S.r.l. reserves the possibility to review or change this document. The updated document can be found on the website www.riwega.com. This document replaces the previous version.