

FDB INT VSK 350

R3

QUICK OVERVIEW: STRENGTHS

The complete adhesive tape for indoors

- Vapour control adhesive tape
- Inside use
- Seals connections on wooden walls airtightly
- Increased weight for high mechanical strength
- Can be over-plastered



①

②

Composition:

- ① Multilayer non-woven PP.PE.PP
- ② Acrylic glue with pre-cutted liner

Features:



Technical data sheet

Glue		modified polyacrylate
Glue carrier material		PP.PE.PP
Thickness	DIN 53855	0,65 mm
Sd value	EN ISO 12572	40 m
Air tightness	EN 1026	$a_n \leq 0,1$
Tensile strength MD/CD*	EN 12311-1	350 / 200 N/50mm
Elongation at break MD/CD*	EN 12311-1	120 / 180 %
Fire reaction class	EN 13501-1	E
Working temperature		-5°C / +40°C
Temperature resistance		-40°C / +80°C
UV stability		do not expose to UV rays
Storage place		dry, protected from UV rays
Storage period		max. 12 months

Codes and measures

Version	Code	Measures (mmxm)	Box (pc)	Pallet (box)
350	02046250	350 (15+167,5+167,5) x25	1	48

*MD = longitudinal CD = transversal

Riwega Srl is not responsible for negligent and improper use of its products