

# FDB INT VSK 350

Acrylic adhesive tape / INTERNAL USE  
Riwega | eternitycomfort

Technical data sheet  
of: 21/09/2023  
Art. 02046250  
Rev.00 of: -

Characteristic	Method	
Adhesive		Modified polyacrylate
Adhesive support		Combination of PP + PE + PP
Liner		White film with Fingerlift, precut to:
		15 mm      167,5 mm      167,5 mm
Roll width		350 mm
Total weight	EN 1849-2	370 g/m <sup>2</sup> (±10 g/m <sup>2</sup> )
Adhesive weight		210 g/m <sup>2</sup> (±10 g/m <sup>2</sup> )
Roll length		25 m
Colour		Pink
Thickness	EN 1849-2	0,65 mm (±0,1mm)
Maximum permissible total deformation		5% (in the area of the unconstrained tape width, otherwise an expansion reserve must be provided)
Tensile strength MD*	EN 12311-1	350 N/50mm (min.330 N/50mm)
Tensile strength CD*	EN 12311-1	200 N/50mm (min.180 N/50mm)
Elongation MD*	EN 12311-1	120% (min.100%)
Elongation CD*	EN 12311-1	180 % (min.150%)
Sd value	EN 1931 / EN 12572	40 m
Airtightness	EN 1026	$a_n \leq 0,1 \text{ m}^3/\text{m}^2\text{h}$
Resistance to water penetration	EN 13984 / EN 1928	W1 Water column > 2000 mm
Working temperature		-5°C / +40°C
Temperature resistance		-40°C / +80°C
Fire reaction class	EN ISO 11925-2: 2010	Class E
UV-stability		Do not expose to UV radiation
Packaging		1 roll
Storage		Store in a cool and dry place, in the original package for max. 12 months

\* MD= Machine Direction; CD= Cross Direction

Riwega S.r.l. reserves the possibility to review or change these technical values. The updated technical data sheet can be found on the website [www.riwega.com](http://www.riwega.com). This data sheet replaces the previous copy.