

VSK Clear 280

43

R2

QUICK OVERVIEW: STRENGTHS

The self-adhesive vapour control layer, transparent and anti-slip

- Vapour control layer, adhesive on the entire surface
- Protection of structures during transport and construction phases
- Transparent, with non slippery surface



new product



Composition:

- 1 Functional film in EVA
- 2 PP non-woven fabric
- 3 Modified acrylic dispersion-based adhesive
- 4 Pre-cutted liner 25 cm

Codes and measures

Code	Code TOP SK	Width (m)	Length (m)	Pallet
02065050	-	1,5	30	1080 m ²
02065051	-	0,75	30	480 m
02065052	-	0,375	30	960 m

Features:



Classification:



Technical data sheet

Material	EVA.PP	
Film	EVA	
Colour	Semi-transparent white	
Mass per unit area	EN 1849-2	290 g/m ²
Glue weight		110 g/m ²
Pre-cutted liner		25 + 125 / 50 / 12,5 cm
Sd value	EN ISO 12572	> 3 m
Water vapour permeability	EN ISO 12572	~ 15 g/m ² /24 h
Watern column	EN 20811	>550 cm
Water tightness	EN 13984	W1
Tensile strength MD/CD*	EN 12311-1	130 / 90 N/50mm
Elongation MD/CD*	EN 12311-1	104 / 90 %
Tear resistance MD/CD*	EN 12310-1	npd**
Fire reaction class	EN 13501-1	E
UV stability		3 months
Temperature resistance		-40°/+100°C
Working temperature		-5°/+40°C

*MD = longitudinal CD = transversal

Riwega Srl is not responsible for negligent and improper use of its products