

# AIR Stop UV

( $\Phi$  15 - 22mm /  $\Phi$  25 - 32mm )

Self-adhesive system with PP base and EPDM collar

Riwega | eternitycomfort

Technical product sheet

of: 02/28/2024

Art. 02203021 /02203022

Rev.00 of: -

Characteristics	$\Phi$ 15 - 22mm	$\Phi$ 25 - 32mm)
	Art.02203021	Art.02203022
<b>Adhesive strip technical data</b>		
Material	PP surface / Acrylic glue	
Color	Black	
Thickness	Approx. 0.32mm	
Weight of the glue	Approx. 210 g/m <sup>2</sup> (DIN EN ISO 536)	
Operating temperature	-30°C / +100°C	
UV stability	Very good	
<b>EPDM technical data</b>		
Material	EPDM	
Color	Black	
Hardness (DIN ISO 48)	60 $\pm$ 5 Shore A	
Density (DIN ISO 1183-1)	Approx. 1.15 g/cm <sup>3</sup>	
Tensile strength (DIN ISO 37)	11.6 MPa	
Operating temperature	-30°C / +100°C	
UV stability	Very good	
<b>General data</b>		
Processing temperature	+5°C / +30°C (workable from -10°C)	
Number of openings	1	
Base size	150 x 150mm	
Internal diameter of the EPDM collar	15mm - 22mm	25mm - 32mm
Type of application	Electrical, plumbing, heating pipes, etc.	
Packaging	Boxes of 10 pieces	
Storage	Store in a dry place at approximately 20°C, protected from light and dust, for max. 24 months	

Riwega Srl reserves the right to modify and/or update the data reported in this document. The updated document can be found on the website [www.riwega.com](http://www.riwega.com). This document cancels and replaces the previous version.