

FDB INT VSK 350 FL

Acrylic adhesive tape / INTERNAL USE
Riwega | eternitycomfort

Technical data sheet
of: 21/09/2023
Art. 02046250
Rev.01 of: 29/05/2024

Characteristic	Method	
Adhesive		Modified polyacrylate
Adhesive support		Combination of PP + PE
Liner		Film with Fingerlift, precut to:
		15 mm 167,5 mm 167,5 mm
Roll width		350 mm
Film weight	EN 1849-2	120 g/m ² (±10 g/m ²)
Total weight (incl. liner)	EN 1849-2	400 g/m ² (±20 g/m ²)
Adhesive weight	EN 1849-2	210 g/m ² (±10 g/m ²)
Roll length		25 m
Colour		Pink
Thickness	EN 1849-2	0,4 mm (±0,1mm)
Maximum permissible total deformation		5% (in the area of the unconstrained tape width, otherwise an expansion reserve must be provided)
Tensile strength MD*	EN 12311-1	200 N/50mm (±20N/50mm)
Tensile strength CD*	EN 12311-1	160 N/50mm (±40 N/50mm)
Elongation MD*	EN 12311-1	140% (120/140%)
Elongation CD*	EN 12311-1	160% (±20%)
Sd value	EN 1931 / EN 12572	40 m
Airtightness	EN 1026	$a_n \leq 0,1 \text{ m}^3/\text{m}^2\text{h}$
Resistance to water penetration	EN 13984 / EN 1928	W1 Water column > 2000 mm
Working temperature		-5°C / +40°C
Temperature resistance		-40°C / +80°C
Fire reaction class	EN ISO 11925-2: 2010	Class E
Hazardous substances	EU 1907-2006	none
UV-stability		3 months
Packaging		1 roll
Storage		Store in a cool and dry place, in the original package for max. 12 months

* MD= Machine Direction; CD= Cross Direction

Riwega S.r.l. reserves the possibility to review or change these technical values. The updated technical data sheet can be found on the website www.riwega.com.
This data sheet replaces the previous copy.