01

ROLL-tech

QUICK OVERVIEW: STRENGTHS

The first, the original

- Under-ridge roll
- Water resistant and UV stable
- Guarantees strong air passage
- Central part in reinforced PP and perfectly adaptable folded aluminium stripe
- Prefolded aluminium edge to increase mechanical resistance





Composition:

- (1) Aluminium with prefolded edge
- (2) Seam
- (3) UV stabilized PP
- (4) Reinforced PP fabric
- (5) Extruded butylic glue
- 6 Silicon liner

Features:



Material

Packaging

Pallet

Pre-folded edge



Technical data sheet









alu.PP.alu

2 pc/box

60 boxes

Air UV Age Tem

Aluminium stripe 0,15 mm 5,00 m Roll legth Central fabric **UV** stabilized PP reinforced PP fabric Central stripe Material assembly glue and seam Extruded butylic glue 140 g/m Air flow (each side) DIN 4108-3 >145 cm²/m UV rays stability stable Ageing resistance >10 years (indirect exp.) Temperature resistance -30°C / +70°C +5°C / +40°C Processing temperature Alu development 1,45 % dry, protected from Storage UV rays, max. +30°C

Codes and measures			
Colours / Measures	310 mm	370 mm	400 mm
Red-brown	01013101	01013601	01014001
Brown	01013102	01013602	01014002
Black	01013103	01013603	-
Beige	-	01013606	-
Grey	01013104	-	-