

FDB INT VSK 350 FL

25

R3

QUICK OVERVIEW: STRENGTHS

The complete adhesive tape for indoors

- Vapour control adhesive tape
- Inside use
- Seals connections on wooden walls airtightly
- Increased weight for high mechanical strength
- Overplasterable surface



Composition:

- ① Multilayer non-woven PP,PE
- ② Acrylic glue with pre-cutted liner

Codes and measures

Version	Code	Measures (mmxm)	Box (pc)	Pallet (box)
350	02046250	350 (15+167,5+167,5) x25	1	48

Features:



Classification:



Technical data sheet

Glue		acrylic with Fingerlift
Glue carrier material		PP,PE
Thickness	DIN 53855	0,4 mm
S _d value	EN ISO 12572	40 m
Air tightness	EN 1026	a _n ≤0,1
Resistance to water passage	EN 1928	W1
Tensile strength MD/CD*	EN 12311-1	200 / 160 N/50mm
Elongation at break MD/CD*	EN 12311-1	140 / 160 %
Water column		>200 cm
Fire reaction class	EN 13501-1	E
Emissions	EMICODE®	EC1 ^{PLUS}
Working temperature		-5°C / +40°C
Temperature resistance		-40°C / +80°C
UV stability		3 months
Storage place		dry, protected from UV rays
Storage period		max. 12 months

*MD = longitudinal CD = transversal

Riwega Srl is not responsible for negligent and improper use of its products