

FDB INT VSK Plus FL

27

R3

QUICK OVERVIEW: STRENGTHS

The complete adhesive tape for indoors, with reinforced surface

- Breathable adhesive tape
- Inside use
- Windtight sealing of door and window joints
- Increased weight for high mechanical strength
- Overplasterable surface



Composition:

- ① Acrylic glue with silicone liner
- ② Multilayer non-woven PPPE
- ③ Acrylic glue with pre-cutted liner

Codes and measures

Version	Code	Measures (mmxm)	Box (pc)	Pallet (box)
85	02046208	85 (25+60) x25	4	72
100	02046210	100 (25+75) x25	4	72

Features:



Classification:



Technical data sheet

Glue		acrylic with Fingerlift
Glue carrier material		PP.PE
Thickness	DIN 53855	0,49 mm
S _g value	EN ISO 12572	40 m
Air tightness	EN 1026	a _n ≤0,1
Tensile strength MD/CD*	EN 12311-1	300 / 55 N/50mm
Elongation at break MD/CD*	EN 12311-1	25 / 135 %
Fire reaction class	EN 13501-1	E
Emissions	EMICODE®	EC1 ^{PLUS}
Working temperature		+5°C / +40°C
Temperature resistance		-40°C / +80°C
UV stability		do not expose to UV rays
Storage place		dry, protected from UV rays
Storage period		max. 12 months

*MD = longitudinal CD = transversal

Riwega Srl is not responsible for negligent and improper use of its products