

# Tape Rapid

03

R3

## QUICK OVERVIEW: STRENGTHS

### The quickest ever

- Single-sided acrylic tape
- Speed up installation because of the absence of the liner
- Next-generation acrylic glue, high adhesion, solvent-free
- Dual use, internal and exterior, thanks to the waterproof surface
- Minimizes waste on the building site



### Composition:

- ① LDPE/PP
- ② Acrylic glue with PET reinforcing

### Codes and measures

| Version    | Code     | Measures (mmxm) | Box (pc) | Pallet (box) |
|------------|----------|-----------------|----------|--------------|
| Tape Rapid | 02040162 | 60x50           | 10       | 80           |

### Features:



### Classification:



### Technical data sheet

|                                 |              |                                            |
|---------------------------------|--------------|--------------------------------------------|
| Glue                            |              | polyacrylate-based disp.                   |
| Glue carrier material           |              | LDPE/PP film                               |
| Reinforcing mesh                |              | YES                                        |
| Protection liner                |              | NO                                         |
| Solvents and emollients         |              | NO                                         |
| Thickness                       | DIN EN 1942  | 0,23 - 0,27 mm                             |
| S <sub>d</sub> value            |              | ~40 m                                      |
| Tear resistance with elasticity | DIN EN 14410 | ≥35 N/25 mm; 400 %                         |
| Bond strength                   | DIN 4108-11  | compliant                                  |
| Resistance to condensation      |              | high                                       |
| Resistance to aging             |              | very high                                  |
| Initial adhesion (Tack)         |              | very high                                  |
| Emissions                       | EMICODE®     | EC1 <sup>PLUS</sup>                        |
| Working temperature             |              | +5°C / +30°C                               |
| Temperature resistance          |              | -30°C / +120°C                             |
| UV stability                    |              | 24 months*                                 |
| Storage place                   |              | dry, protected from UV rays, +18°C / +25°C |
| Storage period                  |              | max. 24 months                             |

\*with reference to the Central European climate  
Riwega Srl is not responsible for negligent and improper use of its products