

USB Protector FH 330/50 GOLD

QUICK OVERVIEW: STRENGTHS

The excellence in the market

- Highly breathable, watertight membrane
- New composition with monolithic TPU film (50 µm) and non-woven fabric in PET
- Extremely resistant to UV rays and extreme weather conditions
- The best of our membranes, guaranteed for 30 years
- Stronghold against laceration or tearing



Composition:

- ① UV stable, water repellent, protective top layer in PET
- ② Film UV50 PUR, monolithic, elastic
- ③ Protective layer in PET

Codes and measures

Code	Code TOP SK	Width (m)	Length (m)	Pallet (m²)
02050218	02020334	1,5	40	960

Features:



Classification:



Technical data sheet

Mass per unit area	EN 1849-2	330 g/m²
Thickness		1,10 mm
S _d value	EN ISO 12572	0,07 m
Water vapour permeability	EN ISO 12572	~ 500 g/m²/24 h
Water column	EN 20811	>800 cm
Heavy rain test	TU Berlin	passed
Resistance to water passage	EN 1928 (Met. A)	W1
Tensile strength MD/CD*	EN 12311-1	500 / 470 N/50mm
Elongation MD/CD*	EN 12311-1	20 / 50 %
Tear resistance MD/CD*	EN 12310-1	400 / 500 N
Fire reaction class	EN 13501-1	E
Exposure to climate factors		52 weeks
Temporary covering	ZVDH	12 weeks
Temperature resistance		-40°C / +120°C

*MD = longitudinal CD = transversal

Riwega Srl is not responsible for negligent and improper use of its products