

FDB Vario VSK Corner FL

Acrylic adhesive pre-folded tape with variable hygrometry
Riwega | eternitycomfort

Technical data sheet
of: 26/01/2026
Art. Nr. 02045816-02045817
Rev.00 del: -



Properties	Normative	FDB Vario VSK Corner FL 75	FDB Vario VSK Corner FL 100
Article		02045816	02045817
Glue		Acrylic with "Fingerlift"	
Material		PET.PA	
Colour		White	
Roll width		75 mm (15 + 60mm)	100 mm (15 + 85mm)
Roll length		25 m	
Total weight	EN 1849-2	400 g/m ² (± 10 %)	
Thickness	EN 1849-2	0,63 mm (± 10 %)	
Maximum permissible total deformation		5% (in the area of the unconstrained tape width, otherwise an expansion reserve must be provided)	
Protection liner		Partial	
Tensile strength MD*	EN 12311-1	300 N/50mm, approx. 220 N/50mm	
Tensile strength CD*	EN 12311-1	80 N/50mm, approx. 65 N/50mm	
Elongation MD*	EN 12311-1	25 %, approx. 15 %	
Elongation CD*	EN 12311-1	135 %, approx. 125 %	
Impermeability class	EN 1928	W1	
Water column		> 2000 mm	
Air tightness	EN 1026	$a_n \leq 0,1 \text{ m}^3/\text{m}^2\text{h}$	
Heavy rain test	EN 1027	> 600 Pa	
S _d -Value	EN 1931 / EN 12572	0,5 m ≤ S _d ≤ 20 m hydrovariable	
Fire reaction	EN ISO 11925-2	Class E	
UV stability		6 months**	
Temperature resistance		- 40°C / +80°C	
Application temperature		- 10°C / +40°C	
Packaging (rolls per box)		6 (6 x 25 m= 150 m)	4 (4 x 25 m= 100 m)
Storage		Store in a clean dry place, in the original box, for a maximum of 12 months	

*MD= longitudinal; CD= transversal / **referring to the Central Europe climate

The Riwega S.r.l. reserves themselves the possibility to review or change these technical values. You can find the technical data sheet on the website www.riwega.com. This data sheet replaces the previous copy.