

# FDB EXT VSK FL

R3

## QUICK OVERVIEW: STRENGTHS

### The complete adhesive tape for outdoors

- Breathable adhesive tape
- Outside use, watertight and windproof sealing of door and window joints
- Fully adhesive surface and pre-cut liner for easy installation
- Ideal for parts that need subsequent shaving



### Composition:

- ① Multilayer non-woven PP.PP
- ② Acrylic glue
- ③ Pre-cutted liner and Fingerlift (protruding liner)

### Codes and measures

Version	Code	Measures (mmxm)	Box (pc)	Pallet (box)
75	02046108	75 (25+50) x25	5	96
100	02046110	100 (25+75) x25	4	96
150	02046115	150 (25+60+65) x25	2	96
350	02046135	350 (15+167,5+167,5) x25	1	48

### Features:



### Classification:



### Technical data sheet

Glue		acrylic with Fingerlift
Glue carrier material		PP.PP
Thickness	EN 1849-2	0,5 mm
S <sub>g</sub> value	EN ISO 12572	0,05 m
Air tightness	EN 1026	a <sub>n</sub> ≤0,1
Resistance to water passage	EN 1928	W1
Tensile strength MD/CD*	EN 12311-1	250 / 120 N/50mm
Elongation at break MD/CD*	EN 12311-1	90 / 150 %
Water column		>200 cm
Fire reaction class	EN 13501-1	E
Working temperature		-10°C / +40°C
Temperature resistance		-40°C / +80°C
UV stability		6 months**
Storage place		dry, protected from UV rays
Storage period		max. 12 months

\*MD = longitudinal CD = transversal

\*\*with reference to the Central European climate

Riwega Srl is not responsible for negligent and improper use of its products