

FDB INT FL

R3

QUICK OVERVIEW: STRENGTHS

The complete adhesive tape for indoors

- Vapour control adhesive tape
- Inside use, windtight sealing of door and window joints
- Fully adhesive surface and pre-cut liner for easy installation
- Ideal for parts that need subsequent shaving



Composition:

- 1 Multilayer non-woven PP/PE
- 2 Acrylic glue
- 3 Pre-cut liner and Fingerlift (protruding liner)

Codes and measures

Version	Code	Measures (mmxm)	Box (pc)	Pallet (box)
75	02046208	75 (25+50) x25	5	96
100	02046210	100 (25+75) x25	4	96
150	02046215	150 (25+60+65) x25	2	96
350	02046250	350 (15+167,5+167,5) x25	1	48

Features:



Classification:



Technical data sheet

Glue		acrylic with Fingerlift
Glue carrier material		PP/PE
Thickness	EN 1849-2	0,4 mm
S _d value	EN ISO 12572	40 m
Air tightness	EN 1026	a _n ≤ 0,1
Resistance to water passage	EN 1928	W1
Tensile strength MD/CD*	EN 12311-1	200 / 120 N/50mm
Elongation at break MD/CD*	EN 12311-1	140 / 180 %
Water column		>200 cm
Fire reaction class	EN 13501-1	E
Emissions	EMICODE®	EC1 ^{PLUS}
Working temperature		-5°C / +40°C
Temperature resistance		-40°C / +80°C
UV stability		3 months**
Storage place		dry, protected from UV rays
Storage period		max. 12 months

*MD = longitudinal CD = transversal

**with reference to the Central European climate

Riwega Srl is not responsible for negligent and improper use of its products