

FDB Vario Corner FL

R3

QUICK OVERVIEW: STRENGTHS

The first pre-folded tape with variable hygrometry

- Acrylic adhesive tape with variable hygrometry
- Pre-folded and partially liner-free to facilitate and speed up the installation
- Indoor & outdoor use, regulates the passage of vapour according to temperature and humidity
- Guarantees air, wind and waterproofing in the laying joint of windows and doors



Composition:

- 1 Multilayer non-woven PET.PA
- 2 Acrylic glue
- 3 Partial liner with Fingerlift (protruding liner)

Codes and measures

Version	Code	Measures (mmxm)	Box (pc)	Pallet (box)
75	02045816	75 (15+60) x25	6	96
100	02045817	100 (15+85) x25	4	96

Features:



Classification:



Technical data sheet

Glue		acrylic with Fingerlift
Glue carrier material		PET.PA
Protection liner		PARTIAL
Thickness	EN 1849-2	0,63 mm
S _g value		0,5 - 20 m
Air tightness	EN 1026	a _n ≤0,1 m ³ /m ² h
Tightness against driving rain	EN 1027	>600 Pa
Tensile strength MD/CD*	EN 12311-1	300 / 80 N/50mm
Elongation at break MD/CD*	EN 12311-1	25 / 135 %
Resistance to water passage	EN 1928	W1
Fire reaction class	EN ISO 11925-2	E
Emissions	EMICODE®	EC1 ^{PLUS}
	CMR regulation	A+
	ISO 16000	compliant**
Working temperature		-10°C / +40°C
Temperature resistance		-40°C / +80°C
UV stability		6 months***
Storage place		dry, protected from UV rays
Storage period		max. 12 months

*MD = longitudinal CD = transversal

**CAM (Criteri Ambientali Minimi Edilizia - IT)

***with reference to the Central European climate

Riwega Srl is not responsible for negligent and improper use of its products